



SUBMITTAL DATA

Airy 29 SEER 24KBTU 230V

Model: GWH24AVEXH-D6DNA1A/I & GWH24AVEXH-D6DNA1A/O

Job Name 	Location 	Date
Purchaser 	Engineer 	
Submitted to 	For 	
Unit Designation 	Schedule No. 	

			
YBE1FB1F	GWH24AVEXH-D6DNA1A/I	GWH24AVEXH-D6DNA1A/O	XE71 (Optional)

GENERAL FEATURES:

- AHRI Certificate: [215278609](#)
- R32 Refrigerant
- High Efficiency DC Inverter Technology
- Compact and Quiet Design
- Wireless Remote with LCD Display
- Wired Controller Options
- I Feel
- Wi-Fi Included
- Low Ambient Cooling down to -20°F (Up to 122°F)
- Low Ambient Heating down to -22°F (Up to 86°F)
- Coil (Indoor and Outdoor) Copper Tube / Aluminum Fin
- Blue Colored Fin - 500 Hrs Salt Spray Test



Tel: +1-604-370-5676
Email: Airtek@greehvac.ca
Website: GREEHVAC.ca

12720 Bathgate Way
Richmond, BC V6V 1Z4
Canada

SPECIFICATIONS & FUNCTIONS:

Model		
Power Supply	VAC / Phase / Hertz	208-230/1/60
Power Supply Mode	-	Outdoor
Cooling Capacity	Btu/h	22000
Heating Capacity	Btu/h	24000
Cooling Power Input	W	1573
Heating Power Input	W	1803
Rated Input	W	4800
Rated Current	A	21.5
EER	(Btu/h)/W	13.98
COP	(Btu/h)/W	13.31
SEER	SEER2	27.5
HSPF	HSPF2	10
Air Flow Volume(H-L)	CFM	765×441×383×212
Dehumidifying Volume	Pint/h	7.4
Application Area	sq ft	495-750

Indoor Unit Model GWH24AVEXH-D6DNA1A/I		
Fan Type	-	Crossflow
Fan Diameter Length (D×L)	mm	φ111.5×830
Cooling Speed	r/min	1450/1150/1100/ 1000/950/900/850
Heating Speed	r/min	1450/1200/1100/ 1050/1000/950/850;
Fan Motor Power Output	W	110
Fan Motor RLA	A	0.85
Motor ratings	hp	0.15
Evaporator Form	-	Aluminum Fin-copper Tube
Evaporator Pipe Diameter	mm	φ7
Evaporator Row-fin Gap	mm	2-1.2
Evaporator Coil Length (L×D×W)	mm	840×25.4×381
Swing Motor Model	-	MP24HF/MP24AQ/MP35CV
Swing Motor Power Output	W	1.5/1.5/2.5
Fuse Current	A	3.15
Set Temperature Range	°F	Cooling:61-86; Heating:46-89
Sound Pressure Level Cooling mode	dB (A)	53/45/44/41/39/38/36
Sound Power Level Cooling mode	dB (A)	65/57/56/53/51/50/48
Sound Pressure Level Heating mode	dB (A)	65/57/56/53/51/50/48
Sound Power Level Heating mode	dB (A)	65/57/55/53/52/51/48
Dimension (W x H x D)	inch	43 45/64×13 42/64×10 8/64
Net Weight	lb.	39.7

Outdoor Unit Model GWH24AVEXH-D6DNA1A/O		
Compressor Manufacturer	-	LANDA
Compressor Model	-	QXFS-B221zX070S
Compressor Oil	-	FW68DA or equivalent
Compressor Type	-	Twin Rotary
Compressor RLA	A	18
Compressor Power Input	W	1775
Outdoor Unit Fan Type	-	Axial-flow
Outdoor Unit Fan Diameter	mm	570
Fan Motor Speed	rpm	800
Fan Motor Power Output	W	90
Motor ratings	hp	0.12
Fan Motor RLA	A	1.7
Air Flow Volume	CFM	2648
Condenser Form	-	-
Condenser Pipe Diameter	mm	φ7
Condenser Rows-fin Gap	mm	2-1.4
Condenser Coil Length (L×D×W)	mm	955×38.1×704
Permissible Excessive Operating Pressure for the Discharge Side	P.S.I.G.	624
Permissible Excessive Operating Pressure for the Suction Side	P.S.I.G.	363
Maximum Allowable Pressure	P.S.I.G.	798
Cooling Operation Ambient Temperature Range	°F	-20~122
Heating Operation Ambient Temperature Range	°F	-22~86
Metering Device	-	-
Defrosting Method	-	-
Sound Pressure Level (H)	dB (A)	62
Sound Power Level (H)	dB (A)	72
Dimension (W×H×D)	inch	39 24/64×29 24/64×16 52/64
Outdoor Unit Net Weight	lb.	115.8
Outdoor Unit Gross Weight	lb.	126.8
Refrigerant	--	R32
Factory Refrigerant Charge	oz	56.4
Connection Pipe Length	ft	24.6
Connection Pipe Gas Additional Charge	oz/ft.	0.4
Outer Diameter of Liquid Pipe	inch	1/4"
Outer Diameter of Gas Pipe	inch	5/8"
Max Distance Height	ft	82
Max Distance Length	ft	131

Functions				
Auto	Self-Diagnosis	Quiet	Energy Saving	Horizontal Auto Swing
Cooling	Lock	I Feel	8°C Heating Mode	Auto Fan
Heating	Filter Dirty Alarm	Intelligent Preheating	Turbo Cooling	Intelligent Defrosting
Dehumidify	Compressor Electric Heater Function	Ventilation	Low Ambient Cooling	Force Defrosting
WIFI	Chassis Electric Heater Function	Dry Anti-mildew Design	Low Ambient Heating	Timer Feature
Sleep Mode	LCD (Back Light)	Several Optional Filters	Low Voltage Startup	Memory
Vertical Auto Swing	LED	Auto Clean	Standby	Multi Speeds



Tel: +1-604-370-5676
Email: Airtek@greehvaca.ca
Website: GREEHVAC.ca


12720 Bathgate Way
Richmond, BC V6V 1Z4
Canada

DIMENSIONS

INDOOR UNIT

Unit: inch


GWH24AVEXH-D6DNA1A/I	
Dimensions	
W	42-7/16
H	13-1/8
D	9-11/16
W1	10-3/16
W2	22-3/32
W3	10-5/32



OUTDOOR UNIT

Unit: inch


GWH24AVEXH-D6DNA1A/O	
DIMENSIONS	
A	35-25/64
B	37-3/4
C	26
D	13-25/64
E	15-7/8
F	22-13/32
G	14-19/32



CLEARANCES

INDOOR UNIT

Minimum clearance



OUTDOOR UNIT

Minimum clearance

