



SUBMITTAL DATA

Single Zone 19 SEER 12KBTU 115V

Model: GWH12ATCXB-A6DNA3A/I & GWH12ATCXB-A6DNA1A/O

Job Name

Location

Date

Purchaser

Engineer

Submitted to

For

Unit Designation

Schedule No.



YBE1FB1F



GWH12ATCXB-A6DNA3A/I



GWH12ATCXB-A6DNA1A/O



XE71 (Optional)

GENERAL FEATURES:

- R32 Refrigerant
- High Efficiency DC Inverter Technology
- Compact and Quiet Design
- Wireless Remote with LCD Display
- Wired Controller Options
- Wi-Fi Included
- Low Ambient Cooling down to 0°F (Range 0°F to 115°F)
- Low Ambient Heating down to -13°F (Range -13°F to 75°F)
- Coil (Indoor and Outdoor) Copper Tube / Aluminum Fin
- Blue Colored Fin - 500 Hrs Salt Spray Tested



Tel: +1-604-370-5676
Email: Airtek@greehvac.ca
Website: GREEHVAC.ca

12720 Bathgate Way
Richmond, BC V6V 1Z4
Canada

SPECIFICATIONS & FUNCTIONS:

Model		
Power Supply	VAC / Phase / Hertz	115/1/60
Power Supply Mode	-	Outdoor
Cooling Capacity	Btu/h	12000
Heating Capacity	Btu/h	12000
Cooling Power Input	W	1231
Heating Power Input	W	1004
Rated Input	W	1650
Rated Current	A	14.64
EER	(Btu/h)/W	9.75
COP	(Btu/h)/W	11.95
SEER	SEER2	19
HSPF	HSPF2	8.5
Air Flow Volume(H-L)	CFM	720/424/353/324/277/247/224/182
Dehumidifying Volume	Pint/h	2.96
Application Area	sq ft	172-258
Controller Model	Remote	YBE1FB1F

Indoor Unit Model GWH12ATCXB-A6DNA3A/I		
Fan Type	-	Crossflow
Fan Diameter Length (D×L)	mm	Φ94×630
Cooling Speed	r/min	1550/1200/1050/980/920/750/500
Heating Speed	r/min	1450/1200/1080/1020/960/900
Fan Motor Power Output	W	35
Fan Motor RLA	A	0.7
Motor ratings	hp	0.05
Evaporator Form	-	Aluminum Fin-copper Tube
Evaporator Pipe Diameter	mm	φ5
Evaporator Row-fin Gap	mm	2-1.3
Evaporator Coil Length (L×D×W)	mm	634×22.8×266.7
Swing Motor Model	-	MP24HF
Swing Motor Power Output	W	1.5/1.5
Fuse Current	A	3.15
Set Temperature Range	°F	61 ~ 86
Sound Pressure Level Cooling mode	dB (A)	47/39/38/35/33/32/27/22
Sound Power Level Cooling mode	dB (A)	57/49/48/45/43/42/37/32
Sound Pressure Level Heating mode	dB (A)	44/39/37/36/34/32/30
Sound Power Level Heating mode	dB (A)	54/49/47/46/44/42/40
Dimension (W x H x D)	inch	32 7/8x10 53/64x7 7/8
Net Weight	lb.	19.8
Gross Weight	lb.	24.3

Outdoor Unit Model GWH12ATCXB-A6DNA1A/O		
Compressor Manufacturer	-	LANDA
Compressor Model	-	FTz-AN108ACBD
Compressor Oil	-	FW68DA or equivalent
Compressor Type	-	Rotary
Compressor RLA	A	14
Compressor Power Input	W	857
Outdoor Unit Fan Type	-	Axial-flow
Outdoor Unit Fan Diameter	mm	400
Fan Motor Speed	rpm	810
Fan Motor Power Output	W	30
Motor ratings	hp	0.04
Fan Motor RLA	A	0.8
Air Flow Volume	CFM	1148
Condenser Form	-	Aluminum Fin-copper Tube
Condenser Pipe Diameter	mm	φ7
Condenser Rows-fin Gap	mm	1-1.2
Condenser Coil Length (L×D×W)	mm	677×19.05×528
Permissible Excessive Operating Pressure for the Discharge Side	P.S.I.G.	624
Permissible Excessive Operating Pressure for the Suction Side	P.S.I.G.	363
Maximum Allowable Pressure	P.S.I.G.	710
Cooling Operation Ambient Temperature Range	°F	0 ~ 118
Heating Operation Ambient Temperature Range	°F	-13~75
Metering Device	-	Capillary
Defrosting Method	-	Automatic Defrosting
Sound Pressure Level (H)	dB (A)	52
Sound Power Level (H)	dB (A)	62
Dimension (WxHxD)	inch	28 13/16x21 27/32x12 63/64
Outdoor Unit Net Weight	lb.	58.4
Outdoor Unit Gross Weight	lb.	63.9
Refrigerant	--	R32
Factory Refrigerant Charge	oz	17.6
Connection Pipe Length	ft	24.6
Connection Pipe Gas Additional Charge	oz/ft.	0.2
Outer Diameter of Liquid Pipe	inch	1/4"
Outer Diameter of Gas Pipe	inch	3/8"
Max Distance Height	ft	40
Max Distance Length	ft	65.6

Functions

Auto	Quiet	Energy Saving	Turbo	Intelligent Defrosting
Cooling	I Feel	8°C Heating Mode	Temperature	Force Defrosting
Heating	Intelligent Preheating	Turbo Cooling	Soft Start	Compressor Electric Heater Function
Dehumidify	Dry Anti-mildew Design	Low Ambient Cooling	Self-Diagnosis	Chassis Electric Heater Function
Air Flow	Several Optional Filters	Low Ambient Heating	Lock	Clock
Auto Fan	Auto Clean	Low Voltage Startup	WIFI	Three Kinds of Sleep Mode
Vertical Auto Swing	Timer Feature	Standby	Multi Speeds	Horizontal Auto Swing
LCD (No Back Light)	LED	Memory		



Tel: +1-604-370-5676
Email: Airttek@greehvaca.ca
Website: GREEHVAC.ca


12720 Bathgate Way
Richmond, BC V6V 1Z4
Canada

DIMENSIONS

INDOOR UNIT

Unit: inch


GWH12ATCXB-A6DNA3A/I	
DIMENSIONS	
W	32-7/8
H	10-7/8
D	7-7/8
W1	7-3/64
W2	18-5/32
W3	7-11/16



OUTDOOR UNIT

Unit: inch


GWH12ATCXB-A6DNA1A/O	
DIMENSIONS	
A	26-37/64
B	28-13/16
C	21-7/8
D	11-7/32
E	13
F	17-29/32
G	12-13/64



CLEARANCES

INDOOR UNIT

Minimum clearance



OUTDOOR UNIT

Minimum clearance

