



SUBMITTAL DATA

Single Zone 19 SEER 24KBTU 230V

Model: GWH24ATEXF-D6DNA3F/I & GWH24ATEXF-D6DNA1F/O

Job Name

Location

Date

Purchaser

Engineer

Submitted to

For

Unit Designation

Schedule No.



YBE1FB1F



GWH24ATEXF-D6DNA3F/I



GWH24ATEXF-D6DNA1F/O



XE71 (Optional)

GENERAL FEATURES:

- R32 Refrigerant
- High Efficiency DC Inverter Technology
- Compact and Quiet Design
- Wireless Remote with LCD Display
- Wired Controller Options
- Wi-Fi Included
- Low Ambient Cooling down to 0°F (Range 0°F to 115°F)
- Low Ambient Heating down to -13°F (Range -13°F to 75°F)
- Coil (Indoor and Outdoor) Copper Tube / Aluminum Fin
- Blue Colored Fin - 500 Hrs Salt Spray Tested



Tel: +1-604-370-5676
Email: Airtek@greehvac.ca
Website: GREEHVAC.ca

12720 Bathgate Way
Richmond, BC V6V 1Z4
Canada

SPECIFICATIONS & FUNCTIONS:

Model		
Power Supply	VAC / Phase / Hertz	208-230/1/60
Power Supply Mode	-	Outdoor
Cooling Capacity	Btu/h	24000
Heating Capacity	Btu/h	24000
Cooling Power Input	W	2010
Heating Power Input	W	1950
Rated Input	W	2600
Rated Current	A	12
EER	(Btu/h)/W	11.9
COP	(Btu/h)/W	12.3
SEER	SEER2	19
HSPF	HSPF2	8.5
Air Flow Volume(H-L)	CFM	1150/677/589/559/500/471/441/412
Dehumidifying Volume	Pint/h	5.28
Application Area	sq ft	248-366
Controller Model	Remote	YBE1FB1F

Indoor Unit Model GWH24ATEXF-D6DNA3F/I		
Fan Type	-	Crossflow
Fan Diameter Length (D×L)	mm	φ111.5×830
Cooling Speed	r/min	1350/1200/1100/1000/950/900/850
Heating Speed	r/min	1350/1200/1100/1000/950/900/850
Fan Motor Power Output	W	50
Fan Motor RLA	A	0.6
Motor ratings	hp	0.07
Evaporator Form	Aluminum Fin-copper Tube	
Evaporator Pipe Diameter	mm	φ7
Evaporator Row-fin Gap	mm	2-1.4
Evaporator Coil Length (L×D×W)	mm	840×25.4×381
Swing Motor Model	-	MP35CP/MP24HF
Swing Motor Power Output	W	2.5/1.5
Fuse Current	A	3.15
Set Temperature Range	°F	61 ~ 86
Sound Pressure Level Cooling mode	dB (A)	51/47/44/41/40/38/36
Sound Power Level Cooling mode	dB (A)	61/57/54/51/50/48/36
Sound Pressure Level Heating mode	dB (A)	51/47/44/41/39/38/36
Sound Power Level Heating mode	dB (A)	61/57/54/51/49/48/46
Dimension (W x H x D)	inch	42 7/16x13 7/64x9 11/16
Net Weight	lb.	33.1
Gross Weight	lb.	39.7

Outdoor Unit Model GWH24ATEXF-D6DNA1F/O		
Compressor Manufacturer	-	LANDA
Compressor Model	-	FTz-SM151AXB
Compressor Oil	-	FW68DA or equivalent
Compressor Type	-	Rotary
Compressor RLA	A	10
Compressor Power Input	W	1330
Outdoor Unit Fan Type	-	Axial-flow
Outdoor Unit Fan Diameter	mm	520
Fan Motor Speed	rpm	800
Fan Motor Power Output	W	50
Motor ratings	hp	0.07
Fan Motor RLA	A	1
Air Flow Volume	CFM	1883
Condenser Form	Aluminum Fin-copper Tube	
Condenser Pipe Diameter	mm	φ7
Condenser Rows-fin Gap	mm	2-1.4
Condenser Coil Length (L×D×W)	mm	839×38.1×616
Permissible Excessive Operating Pressure for the Discharge Side	P.S.I.G.	624
Permissible Excessive Operating Pressure for the Suction Side	P.S.I.G.	363
Maximum Allowable Pressure	P.S.I.G.	754
Cooling Operation Ambient Temperature Range	°F	0 ~ 118
Heating Operation Ambient Temperature Range	°F	-13 ~ 75
Metering Device	-	Capillary
Defrosting Method	-	Automatic Defrosting
Sound Pressure Level (H)	dB (A)	58
Sound Power Level (H)	dB (A)	68
Dimension (WxHxD)	inch	37 23/32x25 63/64x15 53/64
Outdoor Unit Net Weight	lb.	93.7
Outdoor Unit Gross Weight	lb.	103.6
Refrigerant	--	R32
Factory Refrigerant Charge	oz	42.3
Connection Pipe Length	ft	24.6
Connection Pipe Gas Additional Charge	oz/ft.	0.1
Outer Diameter of Liquid Pipe	inch	1/4"
Outer Diameter of Gas Pipe	inch	1/2"
Max Distance Height	ft	82
Max Distance Length	ft	131.2

Functions				
Auto	Turbo	Quiet	Force Defrosting	Auto Fan
Cooling	Temperature	I Feel	Energy Saving	Intelligent Defrosting
Heating	Soft Start	Intelligent Preheating	8°C Heating Mode	Chassis Electric Heater Function
Dehumidify	Self-Diagnosis	Dry Anti-mildew Design	Turbo Cooling	Multi Speeds
Air Flow	Lock	Several Optional Filters	Low Ambient Cooling	Clock
Three Kinds of Sleep Mode	WIFI	Auto Clean	Low Ambient Heating	Standby
Vertical Auto Swing	LCD (Back Light)	Timer Feature	Low Voltage Startup	Memory
Horizontal Auto Swing	LED			



Tel: +1-604-370-5676
Email: Airtek@greehvac.ca
Website: GREEHVAC.ca


12720 Bathgate Way
Richmond, BC V6V 1Z4
Canada

DIMENSIONS

INDOOR UNIT

Unit: inch


GWH24ATEXF-D6DNA3F/I	
Dimensions	
W	42-7/16
H	13-1/8
D	9-11/16
W1	10-3/16
W2	22-3/32
W3	10-5/32



OUTDOOR UNIT

Unit: inch


GWH24ATEXF-D6DNA1F/O	
DIMENSIONS	
A	35-25/64
B	37-3/4
C	26
D	13-25/64
E	15-7/8
F	22-13/32
G	14-19/32



CLEARANCES

INDOOR UNIT

Minimum clearance



OUTDOOR UNIT

Minimum clearance

