



SUBMITTAL DATA

One way Cassette Indoor Unit 20KBTU

Model: GKH(20)DA-D6DNA1B/I

Job Name

Location

Date

Purchaser

Engineer

Submitted to

For

Unit Designation

Schedule No.



GENERAL FEATURES:

- Quiet Operation
- Multi-Speed Fan
- Internal Condensate Drain Pump
- Swing Louver
- Both Wireless & Wired Remote Controllers
- Power Failure Recovery
- Sentry Condensate Overflow Protection
- Decorative Grille (Sold Separately)



Tel: +1-604-370-5676
Email: Airtek@greehvac.ca
Website: GREEHVAC.ca

12720 Bathgate Way
Richmond, BC V6V 1Z4
Canada

SPECIFICATIONS & FUNCTIONS:

Product Model	GKH(20)DA-D6DNA1B/I	
Cooling Capacity	kW	5.6
Cooling Capacity	Btu/h	19100
Heating Capacity	kW	6
Heating Capacity	Btu/h	20500
Air Flow Volume(SS/H/M/L)	CFM	442/383/324/294
Sound Pressure Level (SS/H/M/L)	dB (A)	46/43/40/36
Sound Power Level (SS/H/M/L)	dB (A)	58/55/52/48
Rated Dehumidification Capacity	L/h	2
Dehumidifying Volume	Pint/h	4.23
Rated Voltage	V~	208/230
Rated Frequency	Hz	60
Phases	--	1
Min/Max. Voltage	V	187/253
Cross-sectional Area of Power Cable Conductor	mm ²	1
Recommended Power Cable(Core)	N	4
Fuse Current	A	5
Cooling Power Input	kW	0.045
Heating Power Input	kW	0.045
Cooling Current Input	A	0.3
Heating Current Input	A	0.3
Fan Type	-	Crossflow
Fan Quantity	—	1
Fan Diameter-height	mm	φ 107 – 778
Motor Model	—	FN30E-ZL
Motor Insulation Class	—	E
Motor Safe Class	—	IP40
Fan Motor Speed	r/min	1330/1180/1030/900
Fan Motor Power Output	W	30
Fan motor running current	A	0.3
Evaporator Material	—	Aluminum fin-copper tube
Evaporator Face Area	m ²	0.19
Evaporator Face Area	sq.ft	2.04516
Evaporator Pipe Diameter	mm	φ 7
Evaporator Number of Rows	—	2—3
Evaporator Tube Pitch(a)×Row Pitch(b)	mm	19.05×12.7
Evaporator Fin Pitch	mm	1.6
Evaporator Fins per Inch(FPI)	—	15.875
Evaporator Number of Circuits	—	5in 5out
Evaporator (L × H × W)	mm	790×114.3×25.4 790×114.3×38.1
Evaporator Max. Allowable Pressure	MPa	10
Standard Software and Controller	—	YT1F (MOTO)
Gas Pipe(to indoor unit)	inch	0.5
Liquid pipe	inch	0.25
Connection method	—	Flare Connection
Drain Connection (outer diameter)	inch	1.02362
Dimension of Outline(W x D x H)	inch	38 7/8 x 15 1/8 x 7
Net Weight	lb.	42
Gross Weight	lb.	59.5

Functions	GKH(20)DA-D6DNA1B/I
Auto	YES
Cooling	YES
Heating	YES
Dehumidify	YES
Air Flow	YES
Sleep	Normal sleep mode
Auto Swing(Vertical Auto Swing)	YES
Auto Swing(Horizontal Auto Swing)	YES
Auto Fan	YES
Quiet	NO
I Feel	NO
Anion	NO
Cold Plasma	NO
Intelligent Preheating	YES
Ventilation	NO
Dry Anti-mildew Design	YES
Several Optional Filters (e.g.: Active Carbon)	Optional
Replaceable Front Panel	YES
Timer Feature	YES
Memory	YES
Turbo	YES
Clock	YES
Temperature	YES
Self-Diagnosis	YES
Lock	YES
Intelligent Open-close Panel	YES
Compressor Electric Heater Function	Optional
Chassis Electric Heater Function	Optional
LCD (No Back Light)	YES
Intelligent Defrosting	YES
Force Defrosting	YES
Energy Saving	YES
8°C Heating Mode	YES
Turbo Cooling	YES
Low Ambient Cooling	Optional
Low Ambient Heating	Optional
Low Voltage Startup	YES
Multi Speeds	Speed 4-5
With Access Control System	YES
With Water Pump	YES



Tel: +1-604-370-5676
Email: Airtek@greehvac.ca
Website: GREEHVAC.ca


12720 Bathgate Way
Richmond, BC V6V 1Z4
Canada

DIMENSIONS

INDOOR UNIT

Unit: inch

GKH(20)DA-D6DNA1B/I	
DIMENSIONS	
A	47-1/4
B	43-57/64
C	40-7/16
D	38-55/64
E	18-7/64
F	16-11/32
G	15-5/32
H	10-9/32



CLEARANCES

INDOOR UNIT

Minimum clearance

